



technicoll® 8363 **Solvent for adhesives based on SBR** **(styrene-butadiene rubber)**

Field of application

technicoll® 8363 is a mixture of solvents for diluting adhesives, for cleaning (substrates and tools) and for removing of oil, grease, release agents and adhesives´ residues.

Uncured adhesive residues can be removed with technicoll® 8363. Solid rests or stains of adhesive containing cross linking agents cannot be removed with solvent. Before cleaning, make sure that the substrate to be cleaned will not be damaged by the solvent.

technicoll® 8363 is suitable for cleaning solvent sensitive surfaces of plastics like PVC-plasticised or polystyrene from grease, oil or dust.

Do not use technicoll® 8363 for cleaning skin.

Technical Data Sheets of technicoll® adhesives provide information about appropriate solvents.

Handling data and product data

Base	mixture of solvents
Colour	colourless
Maximum time of storage	At least 3 years when stored in sealed original packaging in cool and dry places.
Preferred storage temperature	+10 °C to +25 °C
Behaviour at low temperature	Not susceptible to frost.

Technical status: 22.12.2015

page 1/1

Deviating information of earlier versions is invalid.

Special notice:

All information given on this data sheet is based on our knowledge and experience at the time of printing. The information is not binding. We advise to determine the suitability of our products with respect to their intended use and method of application. Therefore, a warranty claim cannot be granted.