



### technicoll® 9602 Cleaning and removing agent for technicoll® cyanoacrylates

#### Field of application

---

technicoll® 9602 dissolves and removes residues of technicoll® cyanoacrylates and is also used for cleaning proportioning systems (tools, guns) and tools.

#### Cleaning

---

technicoll® 9602 does not leave any condensed water effected by evaporation of solvent in the dosing system and therefore prevents pre-polymerisation of liquid cyanocrylates. Replace the adhesive bottle of the pressure container with a bottle of technicoll® 9602. Then purge the solvent through the dosing system in an empty cyanoacrylate bottle until no further adhesive will be flushed. Leave the cleaner in the system until the next application. For a new application repeat the procedure (mentioned above) and replace the cleaner with a bottle of adhesive.

Note: Plastics, coatings can be affected!

#### Handling data and product data

---

Base	solvent
Viscosity (+20 °C)	approx. 10 mPas
Colour	colourless
Density (+20 °C)	1.2 g/cm <sup>3</sup>
Maximum time of storage	At least 1 year when stored in sealed original packaging in cool and dry places.
Preferred storage temperature	+10 °C to +25 °C

---

**Technical status: 22.12.2015**

Deviating information of earlier versions is invalid.

page 1/1

#### Special notice:

All information given on this data sheet is based on our knowledge and experience at the time of printing. The information is not binding. We advise to determine the suitability of our products with respect to their intended use and method of application. Therefore, a warranty claim cannot be granted.