

## Seal KITCHEN WORKTOPS - CLEAN AND HYGIENIC

---



### technicoll® 9700

### CLEAN AND HYGIENIC – Sealing straight joints on kitchen worktops with technicoll®

#### Application

---

technicoll® 9700 is especially developed for sealing kitchen worktops made of HPL, Corian® and natural stone. The flexible seal reliably prevents the ingress of moisture.

#### Characteristics

---

|                  |                            |
|------------------|----------------------------|
| Base             | silane-terminated polymers |
| Viscosity        | paste-like                 |
| Initial strength | no                         |
| Gap status       | flexible                   |
| Gap filling      | yes                        |
| Skimming time    | approx. 20 minutes         |
| Hardness         | approx. 55 (Shore A)       |

#### Product Characteristics

---

- Exact dosage and simple application; application aid included in the delivery
- Content of one tube of technicoll® 9700 is sufficient for a straight joint of 60 cm
- Fast curing
- High temperature resistance (for a short time up to +120 °C)
- High adhesive strength on different kinds of materials
- Thixotropic paste sealant, no sagging on vertical areas
- Elastic for tension compensating seals and adhesions
- Does not contain isocyanates or silicone
- Almost shrink-free curing
- Free of solvents and odourless
- High resistance to ageing
- Storable for a long time when closed

#### Special Characteristics

---

- Compatibility to natural stone (grey, black and white only)
- Certificate of Compliance by ISEGA

technicoll® 9700 is specially developed for sealing straight joints on kitchen worktops made of HPL, Corian® and natural stone. The flexible sealing is resistant to cleaning agents, water, as well as grease, oil and reliably prevents the ingress of damaging moisture (e.g. blood from meat, fruit and vegetable juices, etc.) into the straight joint. The joint will be protected for a long time and is easy to clean.

## Application

---

1. Jack through the membrane and screw the black application aid on the top of the tube.
2. Move application aid along the edge of the worktop and simultaneously apply the sealing agent by squeezing equally.
3. Join the worktops immediately.
4. Remove spare and remaining adhesive immediately with a suitable cleaning agent (verify compatibility to the surface of the worktop).

Use the advantages technicoll® offers – high quality raw materials, innovative formulas, technical know-how and excellent consulting.

technicoll® 9700 is available in grey, black, brown and white.



---

**Technical status: 22.12.2015**

Deviating information of earlier versions is invalid.

page 1/1

**Special notice:**

All information given on this data sheet is based on our knowledge and experience at the time of printing. The information is not binding. We advise to determine the suitability of our products with respect to their intended use and method of application. Therefore, a warranty claim cannot be granted.